Questio	Round Numbe	NOTICE:       IARPA will accontrol of the control of the	oth d Government	Government Responses	Chang e to BAA (Yes/N	Paragrap h & Page #
Questio n 1	Roun d 1	The BAA says no internal combustion engine (ICE). I wonder if a solid oxide fuel cell (SOFC) is considered and ICE since a SOFC could consist an internal burner	Page 6	Fuel cells are in scope, provided that they do not comprise a component that is specifically out of scope per section 1.C.4 of the BAA. A heat source for temperature control of a solid oxide fuel cell does not constitute an internal combustion engine.	0)	
Questio n 2	Round 1	Would like some clarification on the meaning of self- contained, which was described in the presentation as: "No external equipment, addition of electricity or fuels, or other external inputs." For the case of a fuel cell, would air count as an external		Air at ambient temperature and pressure does not count as an external input. As noted, all equipment needed for operation (e.g. compression or gas conditioning equipment) will be considered for energy density and power density measurements.		

surroundings. This would be for Track
--

Qu	uestio 3	Roun d 1	We developed a technology based on thermionics that has 10X the efficiency of "historically inefficient" thermionic generators making it competitive with batteries, ICE generators and fuel cells. It is similar to fuel cells in that it converts fuel to electricity with a silent solid state architecture (not moving parts other than a fuel pump if using liquid fuel (but fuel pumps can be avoided if using compressed gas like hydrogen, propane, natural gas etc.) but instead of chemically processing the fuel, the fuel is combusted.	The BAA invites proposals to all types of energy storage and power systems, not just batteries or fuel cells. All proposed technologies must meet the metrics listed in Section 1.E and must not comprise out-of- scope characteristics in Section 1.C.4.		
			requirements perspective it seems			

		like this may be of interest to you but the BAA doesn't mention thermionics as a technology Are you only interested in batteries and fuel cells?				
Questio n 4	Round 1	Is a US University eligible to be a prime recipient? I ask because of the sentence "The Prime contractor must be a U.S. company on the top of page 18 of the BAA	Page 18	Yes, a US University is eligible to be a prime recipient.		
Questio n 5	Roun d 1	We are developing a structural battery that can increase the energy density by up to 30% at the system level without altering the battery chemistry. Currently, we focus on the further development of the technology for		Structural batteries, or any other power solution, are in scope provided they can meet the metrics listed in Section 1.E.		

		Aerospace including the solar-powered perpetual flying UAV. Are structural batteries within the scope of the BAA?	
Questio n 6	Roun d 1	Are maritime/undersea energy sources in scope for the RESILIENCE BAA?	Per section 1.C.1, "The objectives of the program, as stated in the metrics, include performance and properties of power solutions that can be used for multiple applications; no particular form factor is specified nor are any particular devices to be powered envisaged." In the case of undersea applications, no external inputs are permitted, such as water.
Questio n 7	Roun d 1	Technologies to retain cell charge could potentially be integrated into a battery pack with very low SWAP (Size Weight and Power) to achieve the RESILIENCE program objectives specifically in Track 2. One example is the use of thermoelectric	Proposals to the RESILIENCE BAA may include batteries (primary or secondary cells), fuel cells, supercapacitors, or other solutions that convert some form of energy to electricity.         Integrated power systems are within the scope of the program, provided the target metrics of the program are achievable with the proposed integrated power system.

I I I		Т
	generators (TEG's)	
	which have doubled	
	in efficiency in	
	recent years and	
	may have	
	application at the	
	battery pack level	
	but not the cell	
	level. All of the	
	RESILIENCE	
	performance	
	objectives generally	
	appear to apply at	
	the cell level,	
	however creative	
	results that meet the	
	objectives may be	
	obtained by	
	integrating	
	technologies at the	
	battery level. Would	
	the application of	
	TEG's, or other	
	battery pack level	
	technologies be	
	allowed in	
	consideration of the	
	RESILIENCE	
	objectives which	
	appear to be	
	exclusively at the cell	
	level? B) If the	
	TEG's were	

	integrated into a single cell that was part of a pack, and only 1 TEG-enabled "charge retention" cell was needed per some number of cells within a pack, would that be seen as compatible with the RESILIENCE objectives?		
Questio n 8 d 1	alactrolyta containad	Any mathematical model deliverable in Phase 1 must credibly describe how the offeror's delivered power solution can meet all the related metrics in Section 1.E when packaged.	

performance metrics       for Phase 1 when         packaged." Does       this mean that for         Phase I we just have       to demonstrate a         simple coin cell of a       battery formulation         (anode, cathode and       electrolyte) that has         the potential, based       on our mathematical         models, to meet the       Phase I         requirements when       packaged? For         example, we don't       actually have to         meet the Phase I       requirement 600         Wh/kg in the actual       coin. This can't be         as trivial as a coin       that weighs 1 gram         with stored energy       of 0.6 Wh, which         would result in a       ratio of 600Wh/kg         (the "mathematical       model"), including         packaging.       a	1		I.	1
packaged." Does         this mean that for         Phase I we just have         to demonstrate a         simple coin cell of a         battery formulation         (anode, cathode and         electrolyte) that has         the potential, based         on our mathematical         models, to meet the         Phase I         requirements when         packaged? For         example, we don't         actually have to         meet the Phase I         requirement 600         Wh/kg in the actual         coin. This can't be         as trivial as a coin         that weights 1 gram         with stored energy         of 0.6 Wh, which         would result in a         ratio of 600Wh/kg         (the "mathematical         model"), including				
this mean that for         Phase I we just have         to demonstrate a         simple coin cell of a         battery formulation         (anode, cathode and         electrolyte) that has         the potential, based         on our mathematical         models, to meet the         Phase I         requirements when         packaged? For         example, we don't         actually have to         meet the Phase I         requirement 600         Wh/kg in the actual         coin. This can't be         as trivial as a coin         that weighs 1 gram         with stored energy         of 0.6 Wh, which         would result in a         ratio of 600Wh/kg         (the "mathematical         model"), including				
Phase I we just have       to demonstrate a         simple coin cell of a       battery formulation         (anode, cathode and       electrolyte) that has         the potential, based       on our mathematical         models, to meet the       Phase I         requirements when       packaged? For         example, we don't       actually have to         meet the Phase I       requirement 600         Wh/kg in the actual       coin. This can't be         as trivial as a coin       that weighs 1 gram         with stored energy       of 0.6 Wh, which         would result in a       ratio of 600Wh/kg         (the "mathematical       model"), including				
to demonstrate a         simple coin cell of a         battery formulation         (anode, cathode and         electrolyte) that has         the potential, based         on our mathematical         models, to meet the         Phase I         requirements when         packaged? For         example, we don't         actually have to         meet the Phase I         requirement 600         Wh/kg in the actual         coin. This can't be         as trivial as a coin         that weighs I gram         with stored energy         of 0.6 Wh, which         would result in a         ratio of 600Wh/kg         (the "mathematical         model"), including				
simple coin cell of a battery formulation (anode, cathode and electrolyte) that has the potential, based on our mathematical models, to meet the Phase I requirements when packaged? For example, we don't actually have to meet the Phase I requirement 600 Wh/kg in the actual coin. This can't be as trivial as a coin that weighs 1 gram with stored energy of 0.6 Wh, which would result in a ratio of 600Wh/kg (the "mathematical model"), including				
battery formulation (anode, cathode and electrolyte) that has the potential, based on our mathematical models, to meet the Phase I requirements when packaged? For example, we don't actually have to meet the Phase I requirement 600 Wh/kg in the actual coin. This can't be as trivial as a coin that weighs 1 gram with stored energy of 0.6 Wh, which would result in a ratio of 600Wh/kg (the "mathematical model"), including				
(anode, cathode and electrolyte) that has   </td <td></td> <td></td> <td></td> <td></td>				
electrolyte) that has       i         the potential, based       on our mathematical         models, to meet the       Phase I         Phase I       requirements when         packaged? For       i         example, we don't       i         actually have to       i         meet the Phase I       i         requirement 600       Wh/kg in the actual         coin. This can't be       i         as trivial as a coin       i         that weighs 1 gram       with stored energy         of 0.6 Wh, which       i         would result in a       i         ratio of 600Wh/kg       i         (the "mathematical model"), including       i				
the potential, based       on our mathematical         models, to meet the       Phase I         requirements when       packaged? For         example, we don't       actually have to         meet the Phase I       requirement 600         Wh/kg in the actual       coin. This can't be         as trivial as a coin       that weighs 1 gram         with stored energy       of 0.6 Wh, which         would result in a       ratio of 600Wh/kg         (the "mathematical         model"), including				
on our mathematical       models, to meet the         Phase I       requirements when         packaged? For       example, we don't         actually have to       meet the Phase I         requirement 600       wh/kg in the actual         coin. This can't be       as trivial as a coin         that weighs 1 gram       with stored energy         of 0.6 Wh, which       would result in a         ratio of 600Wh/kg       (the "mathematical         model"), including       including				
models, to meet the       phase I         requirements when       packaged? For         example, we don't       actually have to         meet the Phase I       neet the Phase I         requirement 600       Wh/kg in the actual         coin. This can't be       as trivial as a coin         that weighs 1 gram       with stored energy         of 0.6 Wh, which       would result in a         ratio of 600Wh/kg       (the "mathematical model"), including				
Phase I requirements when packaged? For example, we don't actually have to meet the Phase I requirement 600 Wh/kg in the actual coin. This can't be as trivial as a coin that weighs 1 gram with stored energy of 0.6 Wh, which would result in a ratio of 600Wh/kg (the "mathematical model"), including		on our mathematical		
requirements when packaged? For example, we don't actually have to meet the Phase I requirement 600 Wh/kg in the actual coin. This can't be as trivial as a coin that weighs 1 gram with stored energy of 0.6 Wh, which would result in a ratio of 600Wh/kg (the "mathematical model"), including		models, to meet the		
packaged? For example, we don't actually have to meet the Phase I requirement 600 Wh/kg in the actual coin. This can't be as trivial as a coin that weighs 1 gram with stored energy of 0.6 Wh, which would result in a ratio of 600Wh/kg (the "mathematical model"), including		Phase I		
example, we don't actually have to meet the Phase I requirement 600 Wh/kg in the actual coin. This can't be as trivial as a coin that weighs 1 gram with stored energy of 0.6 Wh, which would result in a ratio of 600Wh/kg (the "mathematical model"), including		requirements when		
actually have to         meet the Phase I         requirement 600         Wh/kg in the actual         coin. This can't be         as trivial as a coin         that weighs 1 gram         with stored energy         of 0.6 Wh, which         would result in a         ratio of 600Wh/kg         (the "mathematical         model"), including		packaged? For		
meet the Phase I         requirement 600         Wh/kg in the actual         coin. This can't be         as trivial as a coin         that weighs 1 gram         with stored energy         of 0.6 Wh, which         would result in a         ratio of 600Wh/kg         (the "mathematical         model"), including		example, we don't		
requirement 600       Wh/kg in the actual         coin. This can't be       as trivial as a coin         that weighs 1 gram       with stored energy         of 0.6 Wh, which       would result in a         ratio of 600Wh/kg       (the "mathematical model"), including		actually have to		
Wh/kg in the actual          coin. This can't be          as trivial as a coin          that weighs 1 gram          with stored energy          of 0.6 Wh, which          would result in a          ratio of 600Wh/kg          (the "mathematical          model"), including		meet the Phase I		
Wh/kg in the actual          coin. This can't be          as trivial as a coin          that weighs 1 gram          with stored energy          of 0.6 Wh, which          would result in a          ratio of 600Wh/kg          (the "mathematical          model"), including		requirement 600		
coin. This can't be         as trivial as a coin         that weighs 1 gram         with stored energy         of 0.6 Wh, which         would result in a         ratio of 600Wh/kg         (the "mathematical         model"), including		Wh/kg in the actual		
that weighs 1 gram       i         with stored energy       i         of 0.6 Wh, which       i         would result in a       i         ratio of 600Wh/kg       i         (the "mathematical       i         model"), including       i				
with stored energy       of 0.6 Wh, which         would result in a       in a         ratio of 600Wh/kg       in a         (the "mathematical       in a         model"), including       in a		as trivial as a coin		
with stored energy       of 0.6 Wh, which         would result in a       in a         ratio of 600Wh/kg       in a         (the "mathematical       in a         model"), including       in a		that weighs 1 gram		
of 0.6 Wh, which would result in a ratio of 600Wh/kg (the "mathematical model"), including				
would result in a       ratio of 600Wh/kg       (the "mathematical       model"), including				
ratio of 600Wh/kg (the "mathematical model"), including				
(the "mathematical model"), including				
model"), including				

Questio n 9	Roun d 1	We noted that solutions involving radioactivity were out of scope: more generically, would the program consider power solutions that make use of temporarily activated nuclei to store and release energy as opposed to classical radioactive decay?		No, IARPA will not consider any solutions involving radioactivity. If temporarily activated nuclei were employed to make a power solution, and the final deliverable did not emit ionizing radiation upon delivery for test and evaluation, the power solution would be considered in scope.
Questio n 10	Roun d 1	What does 'scale' for Phase 3 mean?Does "scale to prototype required for Phase 3 of the program" (as stated in the Phase 2 section of BAA) mean you are expecting more than a single cell with positive and negative terminals charged and discharged in a thermal chamber?	Page 5	Scale for Phase 3 means that power solutions must meet all Phase 3 metrics. Per Section 1.C.2, deliverables for Phase 3 have no specific voltage requirements or optimum size (mass or volume), provided that they meet program metrics.
Questio n 11	Roun d 1	Metrics included in Tables 1 and 2 provide a maximum unit temperature		The metrics regarding temperature in Tables 1 and 2 are stated in Celsius and are maximum operating

		during operation of 120°Celsius for Solution Tracks 1 and 2. Can you confirm 120°Celsius (not Farenheit) and clarify that this value represents a maximum operating temperature parameter only and is not a target performance objective?	values. Notional temperatures for testing are provided in Section 1.D.		
Questio n 12	Round 2	The BAA calls for a1-pg summary insection 2 of thetechnical proposalfor a single technicaltrack. Pages 22-23detail items A-E thatmust be included inthe 1-pg technicalsummary for track2, however in all ourprevious IARPAproposals thetechnical summarywas 8-9 pages tocover the same levelof detail in thesummary. In orderto meet the format	Per BAA amendment 1, 4.B.1.b on page 22, The Summary for Track 1 is limited to 5 pages; The Summary for Track 2 is limited to 5 pages; The Summary for Track 1 and 2 combined is limited to 10 pages.		4.B.1.b on page 22,

		requirements and incorporate elements A-E, can IARPA extend the page limit of the summary to 8 or 9 pages instead of 1-pg?			
Questio n 13	Round 2	We need additional clarification on test articles deliverables for Track 1, Phase 3 Prototype. Phase 2 allows delivery of pouch cell as a test article. See excerpt from BAA 1.C.2."As a representative example, a single pouch cell without any attached power electronics that meets all Phase 2 metrics listed would be compliant".Can a pouch cell be compliant with Phase 3 as well?	Yes.		
Questio n 14	Round 2	We have been contacted by multiple parties to participate as subcontractors for	Section 3.A.2 of the BAA states that "organizations may participate as a subcontractor in more than one submission to the BAA." A		

		this solicitation. Is there a restriction in participating in multiple responses?	subcontractor may participate in multiple submissions.
Questio n 15	Round 2	I would like to know if the University of Michigan Energy Institute (UMEI)Battery Lab would qualify as an independent performance validation partner.	No. Per Section 4.A, page 20, the US Army Combat Capabilities Development Command - Command, Control, Communication, Computers, Cyber, Intelligence, Surveillance and Reconnaissance (DEVCOM C5ISR) Center will be supporting Test and Evaluation activities for contracts awarded under this program.
Questio n 16	Round 2	My company is considering applying as a sub-contractor with two separate companies. We plan to propose two completely separate technologies (different anode/cathode pairs). Is this allowed?If we do apply, can we have the same PI on both	Yes. Offerors may apply as prime contractors or sub-contractors on multiple applications. Teaming combinations are not restricted unless otherwise described in the BAA.
Questio n 17	Round 2	applications? Will the RESILENCE	The BAA invites proposals to all types of energy storage and power

		program fund just batteries? Will fuel cell-battery hybrid system be considered?	systems, not just batteries or fuel cells. All proposed technologies must meet the metrics listed in Section 1.E and must not comprise out-of- scope characteristics in Section 1.C.4.
Questio n 18	Round 2	We have some questions about how we might best respond to the BAA, can we setup a quick call to discuss?	No. Unfortunately, IARPA can only respond to questions in writing through the beta.sam.gov website during source selection.
Questio n 19	Round 2	When is the first round due to IARPA for the Resilience effort? We only see the 17 November due date—is this for just the technical and ROM submission?	Per the BAA overview on page 1, the proposal due date for the initial round of selections is November 17, 2020, 4:00 PM EST. Only the Technical Volume is required with the initial submission. If the propsoal is selected for negotiation, the contracting officer will request the detailed cost proposal. (See BAA section 4.B.2 and 5.B).
Questio n 20	Round 2	We are interested in a hybrid solution that includes ''Fuel Cell+Battery+Power Electronics,'' that we will utilize the state- of-the-art battery to achieve the goal.Will this kind of hybrid solution be considered/encourag	Proposals to the RESILIENCE BAA may include batteries (primary or secondary cells), fuel cells, supercapacitors, or other solutions that convert some form of energy to electricity.Integrated power systems are within the scope of the program, provided

		ed to submit for this program to further increase the power density?	the target metrics of the program are achievable with the proposed integrated power system.
Questio n 21	Round 2	What technology readiness level are you looking for?	Offerors may propose technology at any technology readiness level, provided that it can meet the metrics described in Section 1.E.
Questio n 22	Round 2	What is required in terms of teaming?Are you only interested in teams that put together programs that can address all the issues laid out in the BAA? Or is there any interest in developing solutions for smaller chunks of the program?	Proposals to the RESILIENCE BAA must meet all the related metrics in Section 1.E for the relevant track. Teams must demonstrate the ability to meet metrics during all phases of the program.
Questio n 23	Round 2	If a secondary battery is proposed for Track 1 will charging be allowed post shipment at the testing facility? If so will it be upon receipt or will it be after the storage period and	Per Section 1.D., Test 1.1 pages 7-8 of the BAA, the testing protocols described are notional. If there are testing considerations specific to an Offeror's solution that may be incompatible with the notional testing protocols described, these must be described in the Offeror's proposal. Charging a battery upon receipt for Test and Evaluation is an

		immediately prior to testing?	acceptable proposed change to Track 1 notional testing protocols.
Questio n 24	Round 2	Is a single cell acceptable for the packaged power solution for Track 1?	The BAA invites proposals to all types of energy storage and power systems, including a single cell as a packaged energy solution. All proposed technologies must meet the metrics listed in Section 1.E.
Questio n 25	Round 2	You have a maximum battery size and weight, which I interpret to mean we can deliver batteries of any size that are below the maximum but achieve the program metrics (knowing 	Per the BAA section 1.E, there is only a maximum volume and mass constraint on power solutions. No particular size is considered optimal, and there is no minimum volume or mass.

Questio n 26	Round 2	You have several sections about the IP rights. Is it viable to propose a project where one aspect of the project has been published, but we do not have IP ownership of an enabling technology (businesses currently practice with this IP)? Or can we only propose technologies that we fully own or have agreements to use all the IP for?	Per Section 4.B.1.d. of the BAA, "IARPA requires sufficient rights to Intellectual Property (IP) developed or used in the conduct of the proposed research to ensure that IARPA can successfully (a) manage the program and evaluate the technical output and deliverables, (b) communicate program information across Government organizations, and (c) support transition to and further use and development of the program results by Intelligence community (IC) users and others at reasonable cost that is acceptable to the Government." The IP situation of each team (including licensing) is unique. Thus, IP rights will be negotiated with each team on a case by case basis after selection.
-----------------	------------	--	---

Questio n 27	Round 2	Brookhaven National Labs may have facilities or services that can be procured as general technical services for providing additional highly specialized diagnostic capabilities that are not unique to any particular bidder for the RESILIENCE program, and therefore we do not believe that would be against the BAA language indicating that FFRDC's can't act as performers or subcontractors on the proposed effort. Please confirm this services procurement arrangement is acceptable.	Brookhaven and other similar entities (i.e., Other Government Agencies, FFRDC, UARC, GOCOS, etc.) are not eligible to submit proposals or participate as team members on this BAA however, there are instances when these type of entities provide a unique facility, specialized equipment or technical service that is not otherwise obtainable. In such cases, offerors can request use and the Government will determine if the resource can be made available to all offerors as Government Furnished Property/Equipment/Information/S ervice (GFP/GFE/GFI/GFS).Requests for such resources can be submitted during the Q&A period but it may not be possible for the Government to resolve the matter and provide a definitive answer before proposals are due. In this case, the offeror can identify resources required to perform in its proposal (Reference: Section 4.B.1.b and Section 2 E.) along with full details on the matter so that the Government can review.
-----------------	---------	---	--

				Government as GFP/GFE/GFI/GFS, the Government may consider an offeror's request for limited use as a procured service not otherwise available only after an OCI review and determination. It is advised that the offeror have an alternate plan in its proposal in case the Government does not accept the proposed participation of an ineligible entity in its proposal.
Questio n 28	Round 3	The most important question we had was whether a single cell battery was appropriate for your requirements and whether any particular voltage range would be needed on the output.		Per Section 1.C.1, "no particular form factor is specified nor are any particular devices to be powered envisaged." A single cell battery is one possible deliverable, provided that it meets the metrics specified in Section 1.E. Per Section 1.C.2, "deliverables have no specific voltage requirements or optimum size (mass or volume), provided that they meet program metrics."
Questio n 29	Round 3	Are the C rates stated in the Track 1 performance parameters intended	BAA Track 1 Testing,	The metrics stated in section 1.E for Track 1 are intended for all deliverable power solutions, not just batteries. The energy density and

		to be applied to non- battery solutions, and if so, in what manner?	page 8	power density metrics listed may be converted to total energy and power by multiplying these figures times the related volume or mass. C rates may be used to determine the required duration of energy or power output for a given figure of merit.
Questio n 30	Round 3	To support offerors' ability to prepare pricing information, (considering the need for quick turnaround following notification of down select): 1) Does IARPA intend for offerors to submit a Cost Volume in their own format that includes the information set forth in the BAA and Appendix B? 2) In the alternative, will IARPA provide the spreadsheet or other Cost Volume spreadsheet/fillable form as part of this solicitation so offerors may gather	General; BAA 4.B.2, pages 30- 33; Appendix B	Per Section 4.B.2, "[The Cost Proposal] Volume is only required if the Offeror's proposal has been selected for negotiation (see BAA Section 5.B and 5.C). The notification of selection for negotiation will be issued in writing by the [contracting officer] and will include a request to submit the full Cost Volume within 10 business days or as otherwise authorized by the contracting officer." The Cost Proposal Volume structure is outlined in 4.B.2 and Appendix B. For the Estimated Cost Breakdown, Offerors shall submit numerical cost and pricing data using Microsoft Excel. The Excel document shall follow the format provided in Appendix B (Cost Element Sheet) and use intact formulas (not be hard numbered).

		cost information to support the Cost Volume within the timeframes requested?			
Questio n 31	Round 3	Is the information per instructions in 4.B.1.c (L) and (M) to be included in Section 3 of the Technical Volume, or is this consistent with the information provided in the RDMP Attachment (Attachment 11)? Would IARPA consider providing additional page limit for discussion in the applicable section?	BAA 4.B.1.c (L) and (M), page 27; 4.B.1.d Attachme nt 11, page 30	Offerors are required to submit the Research Data Management Plan (RDMP) as an attachment only. Per Section 4.B, Proposal Format and Content, 4.B.1.c. Section 3, Detailed Proposal Information, 4.B.1.d., Section 4: Attachments, and Appendix A.6, the RDMP shall be included as Attachment 11 with a 3 page limit. The RDMP does not count against the page limit of the Technical & Management Proposal volume.	
Questio n 32	Round 3	a) Is the "Maximum Unit Temp during operation of 120°C" technical metric referring to the environmental temperature that the power solution must operate in or is it referring to	BAA Table 1: Technical Metrics for Track 1, page 11.	The metrics regarding temperature in Tables 1 and 2 are maximum operating values. Per Section 1.D, Track 1, Page 8, "Temperature will be measured by a sensor attached to the test article in a position chosen by the T&E team at their sole discretion." Exhaust air must not exceed maximum temperature figures of merit.	

		temperature of the power solution as an interface to the inside of the vehicle? b) If it is at the interface to the inside of the vehicle, does this temperature metric apply to internal vehicle temperature interfaces only? c) Some solutions may have an exhaust system that will send exhaust air that is hotter than 120°C into the air outside the vehicle while the inside of the aircraft interfacing to the power solution would be lower than 120°C. Is this acceptable?				
Questio n 33	Round 3	If the "Maximum Unit Temp during operation of 120°C" metric is in fact referring to the temperature of the power solution as an interface to the	BAA Table 1: Technical Metrics for Track 1, page	Power solutions for Track 1 are envisioned for many applications. Power solutions must meet the metrics in Section 1.E. No further application-specific details are provided.		

	inside of the vehicle, is this requirement derived from a thermal signature requirement or from an internal aircraft max operating temperature due to electronics and other equipment in the vehicles?	11.		
Questio n 34 3	We note that there isa coversheet withinthe IDEAS proposalportal. Should westill complete thecoversheet fromAppendix A of theBAA and include itin the technical andmanagementproposal file?Similarly, there is aseparate upload forthe officialtransmittal letter inthe IDEAS portal.Should we stillinclude this letter inthe technical and		Yes, please complete the coversheet in the IDEAS portal as well as the coversheet included in Appendix A. Per Section 4.C.2., IDEAS will require Offerors to complete a proposal cover sheet within IDEAS at the same time that the Technical and Management Proposal volume is submitted. This is separate and distinct from the Technical and Cost Volume cover sheets referenced in 4.B.1.a. and 4.B.2.a. and provided in Appendices A and B, respectively. Please upload the transmittal letter separately into IDEAS. The cover sheet and transmittal letter may also be included with the Technical & Managment Proposal as they do not count against the page limit for that volume.	

Questio n 35	Round 3	When entering the cost/price information in the coversheet section of the IDEAS portal proposal, should we include all costs for Phases 1, 2, and 3 under "Base Period"? Or should we enter Phase 1 as the Base Period with Phases 2 and 3 as Option Periods 1 and 2, respectively?	Please enter Phase 1 as the Base Period with Phases 2 and 3 as Option Periods 1 and 2, respectively.
Questio n 36	Round 3	What are the "waypoints" in the BAA? Are the "waypoints" similar to "Go/No-Go Points" in the Funding Opportunity Announcement (FOA) from DoE and DoD?	Waypoints are defined in Section1.F.1. Beyond project Waypoints, Section 1.F.3 requires Offerors to deliver test articles on specified dates that meet the metrics described in Section 1.E. Per Section 1.E, ''Performance against the metrics is used to inform decision-making in IARPA research programs; for example, the exercise of options to continue performance under research contracts may be based in large part on achievement of program metrics.''

Questio n 37	Round 3	Is a two week extension to the proposal due date possible, given the IARPA response to question 27?	The RESILIENCE Proposal DueDate is November 17, 2020 at 4pmEST, as stated in the OverviewSection on page 1 of the BAA. Asstated in the BAA, FFRDCs,UARCs, GOCOs and similarorganizations that have a specialrelationship with the Government(e.g., National Laboratories) are noteligible to submit proposals orparticipate as teammates on thisBAA. This general principle has notchanged with our answer to Q.27.
Questio n 38	Round 3	Based on the Government's Response to BAA Q&A # 27- Round 2, can Offerors use Brookhaven National Labs as GFE/GFS for advanced diagnostics equipment and services?	IARPA is aware that unique capabilities exist within some national laboratories, UARCs, GOCOs and the like that are not otherwise obtainable, but may be useful for this program. One such example is the Brookhaven National Laboratory Advanced Synchrotron Light Source-II. At this time, Offerors requesting use of unique capabilities/services offered by this source, shall address their plans in their proposal. It is advised that Offerors include possible alternatives in case this resource is not available (e.g., facility cannot be made available to all Offerors that request use, the Government identifies OCI concerns or the Government determines that this

			organization does not provide a unique capability/service).
Questio n 39	Round 3	For track 1 (primary battery), please confirm if the following deliverables are correct: a. Phase 1 15 testing articles (coin cells), one round test b. Phase 2, 15 	Per Section 1.D, Track 1 requires that a total of 60 test articles be delivered across all three Phases. Specifically, Phase 1 and 3 include one testing round each wherein 15 test articles must be delivered for each round. Phase 2 includes two rounds of testing which requires the delivery of 15 test articles for each round. Track 2 requires that a total of 80 test articles be delivered across all three Phases. Specifically, Phase 1 and 3 include one testing round each wherein 20 test articles must be delivered for each round. Phase 2 includes two rounds of testing which requires the delivery of 20 test articles for each round. Per Section 1.C.1, ''no particular form factor is specified''. The BAA does not specify that the deliverable must be an individual cell, a battery pack or any other technology for either Track.

For track 2 (rechargeable battery), please confirm if the following deliverables are correct:				
a. Phase 1 15 testing articles (coin cells), one round test				
b. Phase 2, 15 testing articles (pouch cells), two round test,				
c. Phase 3, 15 testing articles (power system/battery pack), one round test.				
d. What is the deliverable for phase 3? 15 Individual cells or 15 power systems/packs? The				
BAA only provides maximum mass and volume for phase 2 and 3 "50g and				

30mL, respectively" in table 2. Does Phase 3 not require a normal battery pack but a mini battery pack?		